

Amendment to Barton United States Patent Application #10/074,628

Cancel Claims (1) through (3) and add the following new Claims (4) through (6):

(4) A roll of roofing membrane consisting of non-woven fiberglass scrim covered and saturated with silicone rubber sealant on the top surface to a depth of 1/10 to 9/10 of the way into the thickness of the scrim and covered and saturated with pressure sensitive adhesive on the bottom or underside surface to the remaining 9/10 to 1/10 of the scrim's thickness, wherein the roofing membrane is self-adherent.

(5) The invention recited in Claim (4) wherein the pressure sensitive adhesive is acrylic having a Tg from about -40°C to -50°C.

2 (6) The invention recited in Claim (4) wherein the fiberglass scrim is from about 0.010 inches to 0.040 inches thick.

### Amendment

Cancel Claims (1) through (3) and add the following new Claims (4) through (6):

(4) A roll of roofing membrane consisting of non-woven fiberglass scrim covered and saturated with silicone rubber sealant on the top surface to a depth of 1/10 to 9/10 of the way into the thickness of the scrim and covered and saturated with pressure sensitive adhesive on the bottom or underside surface to the remaining 9/10 to 1/10 of the scrim's thickness, wherein the roofing membrane is self-adherent.

(5) The invention recited in Claim (4) wherein the pressure sensitive adhesive is acrylic having a Tg from about -40°C to -50°C.

(6) The invention recited in Claim (4) wherein the fiberglass scrim is from about 0.010 inches to 0.040 inches thick.

**Claim(s)**

**The invention is claimed as follows:**

(4) A roll of roofing membranc consisting of non-woven fiberglass scrim covered and saturated with silicone rubber sealant on the top surface to a depth of 1/10 to 9/10 of the way into the thickness of the scrim and covered and saturated with pressure sensitive adhesive on the bottom or underside surface to the remaining 9/10 to 1/10 of the scrim's thickness, wherein the roofing membrane is self-adherent.

(5) The invention recited in Claim (4) wherein the pressure sensitive adhesive is acrylic having a Tg from about -40°C to -50°C.

(6) The invention recited in Claim (4) wherein the fiberglass scrim is from about 0.010 inches to 0.040 inches thick.

**Claim(s)**

(4) A roll of roofing membrane consisting of non-woven fiberglass scrim covered and saturated with silicone rubber sealant on the top surface to a depth of 1/10 to 9/10 of the way into the thickness of the scrim and covered and saturated with pressure sensitive adhesive on the bottom or underside surface to the remaining 9/10 to 1/10 of the scrim's thickness, wherein the roofing membrane is self-adherent.

(5) The invention recited in Claim (4) wherein the pressure sensitive adhesive is acrylic having a Tg from about -40°C to -50°C.

(6) The invention recited in Claim (4) wherein the fiberglass scrim is from about 0.010 inches to 0.040 inches thick.